

Q4 Series


Constant Voltage LED Driver

LED恒压驱动器

Features:

- Independent compact design
- Easy press cable lock
- Captured terminal screws
- Protections: opencircuit, shortcircuit, overload, overtemperature
- Simple installation
- SELV equivalent
- Protection class II

- 超小体积，独立式紧凑型设计
- 简便自锁式压线盖
- 螺丝锁紧大接线端子，方便多规格线接驳
- 输出开路，短路，过载和超温保护
- 安装经济便捷
- 符合安全特低电压标准
- 保护等级 II



Parameters:

Model No. 型号	Input voltage 额定电压 (V)	Max. output 功率 (W)	Output voltage 输出电压 (V)	Output current 输出电流 (A)	Power factor 功率因数 (λ)	Efficiency 效率 (%)	No-load power 空载功率 (W)	Ambient temperature 环境温度 ta (°C)	Max. casing temperature 最大外壳温度 tc (°C)	Isolation 隔离	Dimensions LxWxH 尺寸 (mm)	Weight 重量 (g)
Q4-12V-6W	220-240	6	12	0-0.5	0.55C	75	<0.3	-20...+50	80	SELV	81x39x22	50
Q4-12V-12W	220-240	12	12	0-1.0	0.80C	80	<0.3	-20...+50	80	SELV	98x39x22	60
Q4-12V-20W	220-240	20	12	0-1.7	0.80C	82	<0.3	-20...+50	80	SELV	113x44x28	100
Q4-24V-6W	220-240	6	24	0-0.25	0.55C	78	<0.3	-20...+50	80	SELV	81x39x22	50
Q4-24V-12W	220-240	12	24	0-0.50	0.80C	82	<0.3	-20...+50	80	SELV	98x39x22	60
Q4-24V-20W	220-240	20	24	0-0.83	0.80C	83	<0.3	-20...+50	80	SELV	113x44x28	100